



Rush Medium Duty Truck Center, Dallas  
4000 Irving Blvd., Dallas, Texas, 752475816  
Office: 214-631-2050

## Customer Proposal

---

**Prepared for:**

Chris Limongelli  
Republic Services  
14400 N. 87th St, Suite 200  
Scottsdale, AZ 85260  
Office: 480-718-6528  
Mobile: 602-369-1776  
Email: [climongelli@republicservices.com](mailto:climongelli@republicservices.com)

**Prepared by:**

Gary Gibson  
Office: 214-678-5922  
Email: [gibsong@rushenterprises.com](mailto:gibsong@rushenterprises.com)

**Date:** 03/12/2018

**Vehicle:** 2018 F-750 Diesel Base  
Regular Cab

**Quote ID:** R9-2018





## Selected Options

Code	Description
<b>Base Vehicle</b>	
F7D	Base Vehicle Price (F7D)
<b>Engines</b>	
99C	6.7L Power Stroke V8 Turbo Diesel - 270 HP @ 2400 RPM  Includes Engine Exhaust Brake and manual regen capability. Torque: 675 ft.lbs. @ 1600 rpm.  <i>Governed RPM: 3200. Includes CARB clean idle label - may be removed if un-necessary.</i>
425	50-State Emissions
41H	Engine Block Heater, Phillips, 120 Volt/750 Watt
<b>Transmissions</b>	
44G	Ford TorqShift HD 6-Speed Automatic - Double Overdrive, less PTO Provision, less Park Pawl
41A	Transmission Power Take-Off Provision w/LiveDrive Capability
<b>Front Wheels &amp; Tires</b>	
643	Wheels, Front 22.5x8.25 White Powder Coated Steel, 10-Hole  <i>(285.75MM BC) hub piloted, flanged nut, metric mount, 8.25 DC rims; with steel hubs.</i>
TCG	Tires, Front Two 11R22.5G Goodyear Endurance RSA (496 rev/mile)
<b>Rear Wheels &amp; Tires</b>	
663	Wheels, Rear 22.5x8.25 White Powder Coated Steel, 10-Hole  <i>(285.75MM BC) hub piloted, flanged nut, metric mount, 8.25 DC rims; with steel hubs.</i>
RCG	Tires, Rear Four 11R22.5G Goodyear Endurance RSA (496 rev/mile)
<b>Brakes</b>	
67C	Air Brakes - Straight Truck  <i>Meritor Q-Plus with ABS, Bendix Anti-Lock Brake System, 4-channel. Includes 15" x 4" front brakes, dual direct reading air pressure gauges, brake lines color coded nylon, Bendix 13.2 CFM capacity air compressor, instrument panel mounted yellow knob parking brake control valve, automatic slack adjusters front and rear, two rear spring parking air brake chambers mounted on front of rear axle, three drain valves and two air tanks (Reference Body Builders Book for location). Rear brake size and components dependent upon axle selection.</i>
62D	Air Dryer, Bendix AD/IP w/Heater  <i>Mounted left frame rail.</i>

Prices and content availability as shown are subject to change and should be treated as estimates only. Actual base vehicle, package and option pricing may vary from this estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer system. See salesperson for the most current information.



## Selected Options (cont'd)

Code	Description
62F	<b>Brake Chamber Spring Relocated</b> <i>Relocated to rear of rear axle for maximum ground clearance.</i>
158	<b>Trailer Air Brake Package</b> <i>Includes air lines to rear of frame, hand control valve and tractor protection valve.</i>
159	<b>Trailer Connection Socket - 7-Way, Wired for Turn Signals Combined with Stop</b> <i>Mounted at rear of frame, for combined trailer stop, tail, turn (compatible with trailers that use combined stop, tail, turn lights).</i>
<b>Front Axle and Suspension</b>	
43N	10,000 lb. Cap. Non-Driving - Dana E-1002I
61C	<b>Taper-Leaf Springs, Parabolic - 10,000 lb. Cap</b> <i>2-leaf, 62" x 3.15". Also includes, standard duty, dual, double acting shock absorbers.</i>
<b>Rear Axle and Suspension</b>	
475	<b>21,000 lb. Single Reduction - Open - Dana / Spicer 21060S</b> <i>NOTE: When specifying an axle ratio, check performance guidelines for startability and gradeability.</i>
68R	<b>Multi-Leaf Springs - 23,000 lb. Cap</b> <i>11-leaf. Includes 2,000 lb auxiliary springs for load stabilization.</i>
X6B	6.17 Axle Ratio
<b>Wheelbase</b>	
158WB	158" Wheelbase/84" CA/49" AF/246" OAL
<b>Frame</b>	
535	<b>Single Channel - Straight 'C' 15.14 SM, 80,000 PSI</b> <i>1,211,200 RBM. High strength low alloy steel. 10.250" x 3.092" x 0.375" (260.4mm x 78.5mm x 9.5mm). Includes: - GVWR Limit: 37,000 lbs.</i>
765	<b>Bumper, Front - Full Width, Chrome Plated Steel - (Included in (90E) Exterior Appearance Group)</b>
18D	<b>Special Rating GVWR - Limited to 25,999 lb. GVWR</b>
86C	<b>Chrome Grille Surround - (Included in (90E) Exterior Appearance Group)</b>
<b>Exhaust</b>	
91B	<b>Back of Cab, Right Side Outlet, Torpedo-Style</b> <i>Single, horizontal muffler/pipe, inline, right side exhaust with underbody exit, in front of axle.</i>

## Fuel Tanks

Prices and content availability as shown are subject to change and should be treated as estimates only. Actual base vehicle, package and option pricing may vary from this estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer system. See salesperson for the most current information.



## Selected Options (cont'd)

Code	Description
65B	Fuel Tank - LH 50 Gallon Rectangular - Aluminum
12	12 Gal. Single Tank Fuel Fill. Mandatory Charge Applied, Based On Tank Selection
<b>Electrical / Alternator / Battery</b>	
17A	200 Amp Denso SC5 Heavy Duty Alternator <i>Extra heavy duty 12 Volt.</i>
55M	Jump Start Stud - Remote Mounted
63A	Battery - Two 750 CCA, 1500 Total, Includes Steel Battery Box <i>12Volt, Motorcraft.</i>
59C	Body Builder Wiring - At End of Frame, Combined - (ILO Standard - Back of Cab Combined) <i>Includes sealed connectors for 2 ground circuits, with combined left/stop, combined right/stop, back up lamps. Also includes 2 additional pass through wires to cab.</i>
962	Daytime Running Lamps
<b>Seats</b>	
88Y	40/20/40 Fixed Driver & Fixed Passenger w/Unique 20% Fold-Down Console - Vinyl
<b>Cab Interior</b>	
600A	Preferred Equipment Package 600A <i>Includes:</i> <ul style="list-style-type: none"> <li>- Wheel Seals, Front - Oil lubricated, SKF ScotSeal PlusXL Seals</li> <li>- Wheel Seals, Rear - Oil lubricated, SKF ScotSeal PlusXL Seals</li> <li>- Hydraulic Brake System - Bosch HydroMax</li> <li>- Full power with automatic adjustment, 4-channel ABS antilock brake system. Includes 12" x 3" (Bosch) DSSA type rear axle mounted parking brake, Orscheln lever control, right of driver.</li> <li>- Manual Regen Initiation - Driver Interface in Message Center</li> <li>- Engine Exhaust Brake</li> <li>- 200 Amp Denso SC5 Heavy Duty Alternator</li> <li>- Extra heavy duty 12 Volt.</li> <li>- Lights - Roof Marker/Clearance - Amber Lenses, 5 Lights</li> <li>- Tow Hooks, Front (2) - Frame-Mounted, Painted Black</li> <li>- Four Body Builder Switches - Mounted in Center Instrument Panel</li> <li>- With connector access located in engine compartment. Amperages vary by switch: 10, 15, 25, 25.</li> <li>- Floor Covering - Black Vinyl</li> <li>- Intelligent Oil Life Monitor</li> <li>- Steering Column - Tilt</li> <li>- Steering Wheel - Black PVC w/Integral Cruise Control Switches</li> </ul>
588	Radio AM/FM Stereo w/Aux Audio Input Jack & Clock <i>With two speakers.</i>
<b>Cab Exterior</b>	
59A	Horn, Air - Black, Single Trumpet <i>Air solenoid operated, chassis mounted on rail back of bumper.</i>
54C	Mirrors, Dual - Heated Rectangular, XL2020 - 102" Width <i>Integral spot mirror, sail type, manual fold, solid black finish.</i>

Prices and content availability as shown are subject to change and should be treated as estimates only. Actual base vehicle, package and option pricing may vary from this estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer system. See salesperson for the most current information.



## Selected Options (cont'd)

Code	Description
<b>Ship-Thru</b>	
21A	Pre-Delivery Inspection  Selection requires that you also choose either (314) or (31F) or (31V) to have the Inspection performed.
314	Ship-Thru - Manning  MAY be selected w/o adding (21A). For MODIFICATIONS ONLY, Dealer must make arrangements directly with Manning (please use CVT Resources for add. Info).
<b>Fleet Options</b>	
56A	CPA Fleet Incentive
<b>VSO Options</b>	
SPF	Special Paint Formulation (Minimum Quantity 3)
GAB	VSO SPO Code
IHD	VSO Hold Code  This is to put an order on a VSO Hold, so that it does not get scheduled until the VSO dept. releases it.
<b>Interior Colors</b>	
E_03	Gray
<b>Primary Colors</b>	
SFC_01	Enter Special Paint Formulation
<b>Upfit Options</b>	
009911	Decals/Screen Graphics
44459	Stellar CCR Container Carrier with Rotator
55555	F750 Factory Republic Blue Paint
44444	<b>Plus Delivery to Division</b>

Prices and content availability as shown are subject to change and should be treated as estimates only. Actual base vehicle, package and option pricing may vary from this estimate because of special local pricing, availability or pricing adjustments not reflected in the dealer's computer system. See salesperson for the most current information.

<b>Qty</b>	<b>Option PN</b>	<b>Option Description</b>
1.00	CCRX	Stellar CCR - container carrier with 360 degree continuous rotation
1.00	None	No Safety Prop
1.00	HYDCCA3X	Reservoir and 3-section valve bank for container carrier with air controls installed
1.00	PBL	Standard Black Paint
1.00	5355X	PTO, air shift
1.00	56432X	Hydraulic pump for chassis above 19,500# GVW. Use with Dodge and IH chassis.
1.00	46299X	One pair steel fenders for 20,000 to 28,000# GVWR chassis with 22.5 wheels, includes fender brackets, mounting hardware. Mud flaps included with factory installation only
1.00	Included	Mudflaps Included
1.00	62885X	Rear tubular bumper with 30K pintle hitch (does not include pintle hitch)
1.00	57952X	Pintle Hitch - 30,000 lb
	None	No Safety Kit
1.00	10401X	Steel underbody toolbox with overhead door. Dimensions are 18"H x 36"L x 18"D. Features stainless steel automotive-type two-stage latches and stainless steel hinges. Includes mounting brackets. Painted gloss black
	None	No Trailer Plug
1.00	37733X	Service and emergency glad hands with dummies and mounting bracket
<b>1.00</b>	<b>DECAL INSTALL</b>	<b>INSTALL CUSTOMER SUPPLIED DECALS</b>